



## SPESIFICATION :

1. Input : 110/125/220Vac, 1.5A, 1ph, 60Hz  
Output : 12Vdc, 5Amp

2. Automatic Charger Control. (Constant Voltage)

3. Protection :

- a. Breaker Input
- b. Breaker Output
- c. Automatic / Electronic Current Limiter

4. Timer

can be set to 0-30 hours ( boost timer charger )

5. Annunciator

- Charger ON
- Floating
- Equalizing / Boost

6. Panel

Type panel : OUT DOOR, IP65

Dimension :

W x H x D = 40 cm x 50 cm x 30cm

7. After sales services

6 (six) month from delivery date .

\*\* The actual device may differ from the image.



# Battery Charger 24V

Type : TE-BC-1PH-1B-24V10A-THY



\*\* The actual device may differ from the image.

## Specification

<b>Device Name</b>	<b>: BATTERY CHARGER</b>
<b>Type</b>	<b>: TE-BC-1PH-1B-24V10A-THY</b>
<b>Input</b>	<b>: 115/125/220 Vac, 2.7Amp, 60Hz, <math>\pm</math> 10% (selectable)</b>
<b>Voltage Output Setting</b>	<b>: 24 Vdc (adjustable <math>\pm</math> 25%), Constant Voltage</b>
	<b>:</b>
	<b>- Float : 27.6Vdc</b>
	<b>- Boost with 5 Hrs timer : 29.4Vdc</b>
<b>Current Output</b>	<b>: 10 Ampere (max)</b>

The Trustable Partner

**THREDIO**  
engineering